

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 July 2001 (12.07.2001)

PCT

(10) International Publication Number
WO 01/50713 A2

- (51) International Patent Classification⁷: H04M 1/00 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (21) International Application Number: PCT/IB00/01980
- (22) International Filing Date:
29 December 2000 (29.12.2000)
- (25) Filing Language: English (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (26) Publication Language: English
- (30) Priority Data:
09/475,757 30 December 1999 (30.12.1999) US
- (71) Applicant: NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 ESPOO (FI). Published:
— Without international search report and to be republished upon receipt of that report.
- (71) Applicant (*for LC only*): NOKIA INC. [US/US]; 6000 Connection Drive, Irving, TX TEXAS 75039 (US). For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.
- (72) Inventor: DERVARICS, Gergely; Brody Sandor Street 19.1/5, H-1088 Budapest (HU).
- (74) Agents: STOUT, Donald, E. et al.; Antonelli, Terry, Stout & Kraus, LLP, Suite 1800, 1300 N. Seventeenth Street, Arlington, VA 22209 (US).



WO 01/50713 A2

(54) Title: PRINT OPTION FOR WAP BROWSERS

(57) Abstract: The WAP browser in a mobile phone is adapted to permit printing of WML data received and interpreted by The WAP browser. The mobile phone has control circuitry, including a processing unit, a memory connected to the processing unit, and a display. The WAP browser is adapted to interpret received Wireless Markup Language (WML) data and display it on the display. The WAP browser includes a print option which, when selected by the user of the wireless communication device, causes The WML data to be printed.

Best Available Copy

PRINT OPTION FOR WAP BROWSERS

5

TECHNICAL FIELD

The present invention relates generally to mobile phones. In particular, it relates to mobile phones having a WAP browser.

Unlike personal computers, mobile phones typically have unique internal technology and only a small fraction of the resources of a typical desktop or portable computer. This means that the features in the phone are very limited compared to a computer. The reason for this limitation is the size of the phones, ie. the phone has a severe limitation in processing power, memory space, display size and buttons or keys by which a user can request, view and manipulate information obtained from a hypermedia server. Therefore, it is very important that the features in the phone are made as efficient as possible. Also, the relatively high cost for a call from a cellular phone makes it very important to quickly carry out associated functions.

Despite these limitations, mobile phone have nevertheless been growing rapidly in computing power and can now perform many functions in addition to voice telephony. They can, for example, access remote data services, such as banking, stock quotes and weather forecasts, with Short Messaging Service (SMS) and Wireless Application Protocol (WAP).

WAP 1.1 is a result of continuous work to define an industry wide standard for developing applications over cellular communication networks. The WAP 1.1 Specification Sheet is available to the public at www.wapforum.org/what.technical.htm and is hereby incorporated by reference. WAP 1.1 makes it possible to access, for example, the Internet or other kind of information networks provided with hypermedia servers, from an ordinary cell phone supporting WAP. However, The WAP 1.1 Specification Sheet is concerned only with document encoding, transmission and decoding; there is no discussions of the use of downloaded documents.

WAP is very similar to the current Internet standards. The Internet utilizes a Hypertext Markup Language (HTML), e.g. Java Script, a Hypertext Transfer Protocol (HTTP), Transport Layered Security (TLS)/Secure Sockets Layer (SSL), and a Transport Configuration Protocol (TCP)/User Datagram Protocol (UDP). WAP comprises a Wireless Markup Language (WML) corresponding to HTML, a Wireless Session Layer (WSP) corresponding to HTTP, a Wireless Transport Layered Security (WTLS) corresponding to TLS/SSL, and a Wireless Transport Layer (WTP) corresponding to TCP/UDP. THE core of WAP is WML and WML Script, which are interpreted by using a browser resident on The mobile device. Furthermore, WAP comprises different bearers like, for example, SMS, USSD, and CDMA. It is also possible to implement different kinds of services and

applications in WAP, e.g. Value Added Services (VAS).

Although software applications in the personal computer environment are well developed and robust, the software in a mobile phone can sometimes be written in a relatively uncommon language and programmers may have difficulty working with that language. Consequently, each new function in the phone, even functions which are relatively simple in other environments, like storing and printing data, is difficult to implement since it must utilize very limited resources, involves low level programming and depends on the phone's internal architecture.

Mobile phones also lack the serial, parallel, and USB ports, ethernet connections and other interfaces common on personal computers. There are thus additional difficulties in carrying out functions, like printing, that require an external device. While there are some wireless infrared methods of transferring data between mobile devices, such as IrCOMM (www.irda.org) and Bluetooth (www.bluetooth.com), they have underlying protocols which define standard ways to transfer the data. These methods do not define a protocol that works at the uppermost data layer and is understood by both devices. Consequently, there are difficulties in printing data in WML format. Other devices, such as Personal Digital Assistants (PDAs), can print by themselves or can print through a desktop computer. But these devices utilize a HTML browser, such as Pocket Explorer from Microsoft, rather than a WAP/WML browser and can thus use the printing functions available in such a conventional browser.

Printing mobile phones with browsers is also difficult since the visual part of user interfaces for mobile phones is not standardized and WML content can be shown in different ways. Every mobile phone breaks the text and other parts of the content into several lines in its own way. Printers have much wider lines than mobile phones and can print the text in a more readable format.

The present invention addresses mobile phones with browsers. There are several different aspects and objects of the invention. However, the invention is not limited thereto. A particular implementation of the invention may apply an combination of the aspects and objects of the invention, such that some aspects and objects of the invention may be practiced in a particular implementation of the invention even though some other aspects and object are not practiced in the particular implementation.

An object of the invention is to provide optimal data handling extensions for the browser of a mobile phone to allow additional printing functions. An embodiment of the invention adds the printing functions in the source code of the browser.

One object of the invention is to provide printing capabilities for a mobile phone as a software functionality without adding additional hardware (such as button on a keypad). For example, an embodiment of the invention is implemented by being included in the operating system

software of the mobile phone.

Another object of the invention is to make use of a printing facility that is well integrated into the mobile phone and which can be shared by different sub-systems of the device. For example, one embodiment of the invention extends the same printing facility used for printing a phone book or calendar to additionally print The WML content from a WAP browser as well.

A further object of the invention is to provide a mobile phone that is capable of printing a variety of types of data, including WML content, on a separate printer via a direct infrared communication link to that printer.

According to an exemplary embodiment of the invention, The WAP browser in a mobile phone is adapted to permit printing of WML data received and interpreted by The WAP browser. The mobile phone has control circuitry, including a processing unit, a memory connected to the processing unit, and a display. The WAP browser is adapted to interpret received Wireless Markup Language (WML) data and display it on the display. The WAP browser includes a print option which, when selected by the user of the wireless communication device, causes The WML data to be printed.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a graphical illustration of the preferred implementation of the invention to print data from a WAP device.

Fig. 2 is a generalized block diagram of a mobile phone with a WAP browser and a display according to one aspect of the invention.

Fig. 3 is a block diagram useful for illustrating a process of decoding and printing data in a mobile phone according to an example embodiment of the invention.

BEST MODE FOR CARRYING OUT THE INVENTION

The foregoing and a better understanding of the present invention will become apparent from the following detailed description of example embodiments and the claims when read in connection with the accompanying drawings, all forming a part of the disclosure of the invention. While the foregoing and following written and illustrated disclosure focuses on disclosing example embodiments of the invention, it should be clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the spirit and scope of the present invention being limited only by the terms of the claims in the patent issuing from this application.

The preferred embodiment of the invention seeks to provide an integrated printing extension for a WAP browser in a mobile phone. The invention of course is not limited to such a specific

embodiment. It is more broadly directed to any of a diverse set of WAP-enabled mobile phones having a user agent for interpreting downloaded data.

Fig. 1 is a graphical illustration useful for showing an application of the preferred embodiment of the invention and for contrasting it with a conventional method. According to the invention, WML formatted content downloaded by a WAP device 100 is printed on a separate printer 120 via an infrared link 110. This is in contrast to the conventional process of downloading HTML format data on a personal computer (PC) with internet browser 130 and printing it via an ethernet, serial or parallel interface.

The WAP device 100 differs from the personal computer with internet browser 130 in that it generally has a less powerful CPU, less memory, restricted power consumption, smaller displays and more limited input devices. The cellular network differs from the Internet network in that it generally has less bandwidth, more latency, less connection stability and less predictable availability.

Communication between WAP device 100 and a WAP gateway, connected in turn to at least one web server, is according to the Wireless Application Protocol (WAP). WAP specifies an application framework and network protocols for cellular terminals such as mobile telephones, pagers, and personal digital assistants. WAP brings Internet content and advanced data services to cellular terminals. It is optimized for narrow bandwidth bearers with potentially high latency and is optimized for efficient use of WAP device resources. WAP can work across differing cellular network technologies and bearer types (GSM, CDMS, SMS).

WAP defines a set of standard protocols that enable communication between mobile terminals and network servers. WAP uses a standard naming model according to which standard Internet URLs are used to identify content on servers. It also uses content typing. All WAP content is given a specific type consistent with WWW typing which allows a cellular terminal to correctly process the content based on type. WAP also uses standard content formats and standard communication protocols.

Mobile Phone Architecture

WAP device 100 is preferably implemented as a mobile phone having a keypad, a display, an on/off button, a speaker, and a microphone. It is preferably adapted for communication via a cellular telecommunication network, e.g. a cellular network. However, the phone can also be designed for a cordless network. The keypad has a first group of twelve alphanumeric keys, by means of which the user can enter a telephone number, write a text message (SMS), write a name (associated with the phone number), etc. Each of the keys is provided with a figure "0-9" or a sign "#" or "*", respectively. In alpha mode, each key is associated with a number of letters and special signs used in

various resources of the mobile phone, and provides communication facilities for various peripheral units, such as the printing facility.

Control circuitry 203 communicates with a standard cellular transceiver 201 connecting it to, and adapted to send/receive a request/respond to/from, a telecommunication network. The audio part
5 speech-decodes the signal, which is transferred from the control means to the carpiece via a D/A converter (not shown). Control circuitry 203 also communicates with an infrared (ir) or Bluetooth wireless port 202 enabling it to directly send data to another device via a wireless infrared connection. Port 202 contains the appropriate drivers for establishing a connection with another
10 device, such as a printer. Although display 207 is shown separately in Fig. 2 for simplicity, it is preferably formed integrally with the mobile phone.

The control circuitry 203 monitors the activity in the phone and controls the display in response thereto. Therefore, it is the control circuitry 203 which detects the occurrence of a state change event and changes the state of the phone and thus the display text. A state change event may
15 be caused by the user when he activates the keypad including the navigation key, and these types of events are called entry events or user events. However, the network communicating with the phone may also cause a state change event. This type of event and other events beyond the user's control are called non-user events. Non-user events comprise status change during call set-up, change in battery voltage, change in antenna conditions, message on reception of SMS, etc.

20 Browser Operation

A Wireless Application Environment which forms an upper layer of The WAP stack includes a browser application, also called a micro-browser. The browser uses Wireless Markup Language (WML), a lightweight markup language, and WML Script a lightweight scripting language. The
25 browser application is arranged to establish a session by reading an item in flash ROM 205. The user interface is connected to the browser application having a display for displaying content and user input means for control the browser. The browser can be arranged in flash ROM 205 or in SIM card 206.

A preferred embodiment of the invention is that a script in flash ROM 205 can activate or download linking applications, i.e., an application which makes it possible to receive and/or transmit
30 different types of data to WAP device 100. For example, the different types of data packets can be a particular text format, software programs, picture formats. This allows the processing power of the terminal to be restricted, allows a standard WAP browser to be used and provides flexibility for new features. This is preferably done by creating extensions to WML and WML script. Thus, the script can make it possible to access data packets, which might not be supported by the software in the

terminal, by downloading the appropriate application, supporting the type of data format, directly to the terminal. The content of the data packet can be displayed, stored, interpreted and/or printed by infrared transmission directly to the printer.

5 It is preferable to provide one or more distinct linking applications in flash ROM 205 of WAP device 100 prior to establishing communications. This is typically done during the manufacture of WAP device 100, wherein the linking application can be a software program controlling access to the server. A variety of other software applications can also be included and stored in flash ROM 205.

10 In another aspect of the invention, RAM 204 is arranged to copy items from a session. Typically, RAM 204 can be a cache memory, which means that the items from the latest session can be temporarily saved in the second memory. As an alternative, the items from a session can be saved in a permanent storage memory, which means that the user is able to confirm if the items are going to be saved or deleted. The permanent storage memory can be SIM card 206 and/or flash ROM 205.

15 When the mobile phone of the preferred embodiment is activated, the user may select a browser menu on a display controller by the browser application. In this browser menu the user can choose to establish a session to a server. To establish the session the user selects the service connected to the server from the menu. The selection is done by e.g. pressing on one of the soft keys. When the server sends requested information, it is interpreted by the browser application and displayed on display 207. Preferably, display 207 is an liquid crystal display (LCD).

20

User Interface

25 Display 207 of WAP device 100 can be controlled by control circuitry 203. When the phone is activated and awaiting an action, e.g., an incoming or outgoing call, an idle mode is displayed. In the bottom of the display, there is two items which are denoted as "Menu" 55 and "Names" 60. If the user selects "Names", he/she can e.g. access a built in phone book. If the user selects "Menu" 55, he/she can select among several different menus. The actual selection of features in the bottom of the display, like "Menu" and "Names", can be selected by means of the soft keys. One of the menus can be the next display called "Browser": If the user chooses to use this menu, he/she can access different telecom related information services, e.g. Internet, using WAP.

30

During operation, the browser displays a number of options on display 207 of the mobile phone. These options may include the conventional options of clear cache, exit, bookmarks, home page, etc. In an exemplary embodiment, these options are shown at a place on the display that is associated with the soft keys of the phone. The print option is preferably shown at the same place where these other options are shown and selected.

When the print option is selected, the print facility feature integrated into the source code of the operating system causes the control circuitry 203 to perform the various functions necessary to accomplish printing of the received WML data. First, the control circuitry 203 accesses the area in memory where the browser stored the downloaded WML data. The data is preferably stored in the memory in encoded format. An additional area is then set aside in memory where The WML data is prepared to be printed. When the user chooses to print a page, the program decodes The WML data again but into the additional area set aside in memory instead of the display. If necessary, the print facility utilizes the identifier of The WML data also stored in the memory and representing different types of data as discussed above.

An example of the operation of the printing facility is provided in Fig. 3. While a block diagram form is employed in Fig. 3 to represent The WML decoder 301 and other elements of the printing facility, it should not be misinterpreted that the elements are necessarily implemented as hardware components. The blocks are chosen so as to best illustrate the parts of the process and the various elements can be implemented in any number of different ways, including, but not limited to, software.

WML decoder 301 receives a decode request for downloaded WML data from cellular transceiver 201 of the mobile phone. The WML data may be immediately decoded or may be temporarily stored in WML cache 302 prior to decoding. The WML cache 302 is preferably organized in sizes so as to facilitate the quick storage and retrieval of entire pages of WML data at one time. A display module 303 includes a display memory 303-1 and user interface routines 303-2 for the display 207. The user interface routines 303-2 handle the user actions and input fields of the user interface and translates them so that they can be used by the operating system software of the mobile phone. A printing module 304 contains a print buffer 304-1 and printing routines 304-2. The printing routines 304-2 are preferably part of the browser, but utilize the appropriate application programming interface (API) of the operating system software to implement the printing facility of the mobile phone.

The WML decoder 301 is operated in conjunction with The WML cache 302, display module 303 and printing module 304 to print The WML data when the print option of the browser is selected by the user. In particular, WML decoder 301 supports different line lengths, output buffers and handlers. This is especially important since the character width of the display 207 controlled by display module 303 is typically much narrower than the character width of the printing facility controller by printing module 304. WML decoder 301 makes the necessary conversions and wrap-arounds so that the decoded WML data displayed on display 207 can be suitably printed.

Printing to an external printer is carried out by directing control circuitry 103 to try to

establish a connection to a printer via the infrared port 202. Preferably, the infrared communication is carried out using Bluetooth wireless transfer. The driver for this service is integrated into the source code of the pre-installed operating system since communication with an infrared port is not normally required for a mobile phone. In one aspect of the invention, the driver is able to transmit
5 data via infrared port 202 from sources other than the browser. For example, it may be used to send out data for printing a phonebook, calendar, etc. If the connection to the printer is established, the program sends a page of data to the printer. If the infrared port 202 is unable to make a connection to the printer or there isn't any receiving printer, an error message is displayed to alert the user.

While the foregoing has described what are considered to be example embodiments of the
10 invention, it is understood that various modifications may be made therein and that the invention may be implemented in various forms and embodiments, and that it may be applied in numerous applications, only some of which have been described herein. It is intended by the following claims to claim all such modifications and variations.


CLAIMS

- 1 1. A mobile phone comprising:
2 control circuitry, including a processing unit;
3 a memory connected to the processing unit;
4 a display; and
5 a Wireless Application Protocol (WAP) browser adapted to interpret received Wireless
6 Markup Language (WML) data and display said WML data on said display,
7 wherein said WAP browser includes a print option which, when selected by the user of the
8 mobile phone, causes said WML data to be printed.
- 1 2. The mobile phone recited in claim 1, wherein The WML data is stored at a location in
2 said memory prior to selection of the print option.
- 1 3. The mobile phone recited in claim 2, wherein said WML data is read from said location in
2 said memory when said print option is selected and is decoded prior to printing.
- 1 4. The mobile phone recited in claim 1, wherein The WML data is printed via a direct
2 infrared interface to a printer.
- 1 5. The mobile phone recited in claim 1, wherein The WML data is transferred to the printer
2 using Bluetooth wireless transfer.
- 1 6. The mobile phone recited in claim 1, wherein the print option is selected by the user in
2 accordance with a menu displayed on said display.
- 1 7. The mobile phone recited in claim 6, wherein the user selects the print option by pressing
2 a soft key associated with the menu.
- 1 8. The mobile phone recited in claim 1, wherein the print option utilizes a printing facility
2 which can print data from sources other than said WML data interpreted by said WAP browser.
- 1 9. The mobile phone recited in claim 8, wherein the printing facility can also print a phone
2 book or calendar stored in the mobile phone.


1 10. The mobile phone recited in claim 8, wherein the character width of lines in said display
2 is narrower than the character width of lines printed by said printing facility.

1 11. The mobile phone recited in claim 8, wherein the printing facility is included in
2 operating system software of the mobile phone.

1/3




2/3



3/3

FIG. 3



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 July 2001 (12.07.2001)


PCT

(10) International Publication Number
WO 01/50713 A3

- (51) International Patent Classification⁷: H04L 12/28, 12/56, 29/06, 29/08
- (21) International Application Number: PCT/IB00/01980
- (22) International Filing Date:
29 December 2000 (29.12.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/475,757 30 December 1999 (30.12.1999) US
- (71) Applicant: NOKIA CORPORATION [FI/FI]; Keilalahdenie 4, FIN-02150 ESPOO (FI).
- (71) Applicant (for LC only): NOKIA INC. [US/US]; 6000 Connection Drive, Irving, TX TEXAS 75039 (US).
- (72) Inventor: DERVARICS, Gergely; Brody Sandor Street 19.1/5, H-1088 Budapest (HU).
- (74) Agents: STOUT, Donald, E. et al.; Antonelli, Terry, Stout & Kraus, LLP, Suite 1800, 1300 N. Seventeenth Street, Arlington, VA 22209 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: PRINT OPTION FOR WAP BROWSERS



(57) Abstract: The WAP browser in a mobile phone is adapted to permit printing of WML data received and interpreted by The WAP browser. The mobile phone has control circuitry, including a processing unit, a memory connected to the processing unit, and a display. The WAP browser is adapted to interpret received Wireless Markup Language (WML) data and display it on the display. The WAP browser includes a print option which, when selected by the user of the wireless communication device, causes The WML data to be printed.

WO 01/50713 A3



(88) Date of publication of the international search report:
28 March 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No

PC/IB 00/01980

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/28 H04L12/56 H04L29/06 H04L29/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
Y	WO 99 45684 A (NOKIA MOBILE PHONES LTD ;NYKAENEN PETRI (FI)) 10 September 1999 (1999-09-10) abstract page 1, line 4 -page 5, line 10 page 6, line 26 - line 33 page 8, line 11 -page 9, line 24 page 11, line 7 - line 18 page 12, line 17 - line 29 figures 1,2A,2B,3A,4 ---	1-11
Y	WO 99 00968 A (ERICSSON TELEFON AB L M) 7 January 1999 (1999-01-07) abstract page 1, line 9 -page 6, line 2 page 7, line 28 -page 9, line 30 page 12, line 16 -page 13, line 5 page 18, line 25 -page 19, line 26 --- -/--	1-11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referred to in oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *S* document member of the same patent family

Date of the actual completion of the international search

1 November 2001

Date of making of the international search report

07/11/2001

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 240-2040, Tx: 31 651 epo nl,
Fax: (+31-70) 240-2016

Authorized officer

Vaskimo, K

INTERNATIONAL SEARCH REPORT

International Application No

PC1/IB 00/01980

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 840 492 A (NOKIA MOBILE PHONES LTD) 6 May 1998 (1998-05-06) abstract column 1, line 1 -column 3, line 14 column 3, line 40 -column 4, line 16 column 4, line 44 -column 5, line 30 ---	1-3
A	EP 0 877 531 A (NOKIA MOBILE PHONES LTD) 11 November 1998 (1998-11-11) page 2, line 3 -page 5, line 46 page 8, line 46 -page 9, line 2 -----	1,6,7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 00/01980

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9945684	A	10-09-1999	FI 980485 A	04-09-1999
			AU 2627199 A	20-09-1999
			EP 1060594 A2	20-12-2000
			WO 9945684 A2	10-09-1999
WO 9900968	A	07-01-1999	SE 512474 C2	20-03-2000
			AU 8135598 A	19-01-1999
			SE 9702472 A	28-12-1998
			WO 9900968 A1	07-01-1999
EP 0840492	A	06-05-1998	FI 964425 A	05-05-1998
			EP 0840492 A2	06-05-1998
			JP 10190866 A	21-07-1998
			US 5953675 A	14-09-1999
EP 0877531	A	11-11-1998	US 6029065 A	22-02-2000
			AU 7134498 A	27-11-1998
			EP 0877531 A2	11-11-1998
			WO 9851100 A2	12-11-1998

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.